

Standby (kVA)	Prime (kVA)	Engine Model	Cylinders	RPM	Hz	Volts	Fuel Tank (L)	Fuel Cons. (L/hr)	Oil Sump (L)	L (mm)	W (mm)	H (mm)	Weight (kg)
150	165	1106C-E66TAG3	6 Inline	1500	50	380	279	32.5	19	2701	900	1545	1453
200	220	1306C-E87TAG4	6 Inline	1500	50	380	350	49.4	26.4	2960	1003	1718	2052
250	275	1306C-E87TAG6	6 Inline	1500	50	380	350	58.9	26.4	2960	1003	1718	2252
350	400	2306A-E14TAG2	6 Inline	1500	50	380	791	69.4	68	3601	1100	2070	3366
500	550	2506A-E15TAG2	6 Inline	1500	50	380	928	97.2	68	3700	1100	2143	3958
600	660	2806A-E18TAG1A	6 Inline	1500	50	380	1000	118.4	55.5	4111	1536	2246	4787
800	880	4006-23TAG33A	6 Inline	1500	50	380	1494	163	123	4280	1912	2277	6370
1000	1100	4008TAG2A	8 Inline	1500	50	380	N/A	215.4	166	4790	2036	2235	7568
1250	1375	4012TWG2A	12V	1500	50	380	N/A	257.1	173	4820	1895	2424	9255
1500	1650	4012-46TAG2A	12V	1500	50	380	N/A	296.6	173	5095	1900	2435	9910
2000	2200	4016TAG2A	16V	1500	50	380	N/A	423.6	238	5725	2300	3020	15700

Specifications are subject to change without notice.

About the Perkins Generator Range

The Perkins Diesel Generator Range is built to meet the power demands of diverse industries including manufacturing, healthcare, construction, oil & gas, telecoms, and commercial facilities. Operating at 1500 RPM and 50Hz, these generators provide optimal efficiency, reduced engine wear, and consistent output under varying load conditions.

Key Advantages:

- High fuel efficiency and low operating cost
- Robust build for continuous and standby applications
- Stable voltage and frequency output
- Wide capacity ranges from 150 kVA to 2000 kVA
- Backed by Movi Power's professional installation and after-sales support

Request a Quote: 0809 977 7707 / sales@movipower.com / www.movipower.com

